

Brief spec.; 19.0" SXGA Super High Bright & LED Backlight model

Features

- Super High Bright 1500cd/m²
- LED Lifetime 100,000h
- Natural Color Matrix

| | | |
|-----------------------------------|--|-------|
| TYPE NAME | AA190EA01 | |
| Schedule | CS: 11/3Q, MP: 11/4Q | |
| Screen Size / Resolution | 48.2cm (19-inch) / SXGA | |
| Active Screen Area Size [mm] | 376.3(H) x 301.1(V) | |
| Pixel Number | 1280(H) x 1024(V) | |
| Pixel Pitch [mm] | 0.294(H) x 0.294(V) | |
| Contrast Ratio | 800:1 | |
| Brightness [cd/m ²] | 1500 (IF=130mA) | |
| Viewing Angle (CR>10) [°] | -80~80(H), -80~80(V) | |
| Viewing direction | Higher Contrast ratio: 6 o'clock Less gray scale reversal: 12 o'clock | |
| Colors | 262k(6bit/color) / 16.7M(8bit/color) | |
| Color Saturation (vs. NTSC) [%] | 50 | |
| Natural Color Matrix | Yes | |
| Backlight | LED (Unreplaceable) | |
| Lamp/LED Life [h] | Typ.100,000 | |
| Interface | LVDS 2ch | |
| Power Consumption [W] | TBD | |
| Power Supply [V] | 5.0 | |
| Reverse Scan | Available | |
| Module Outline Dimensions [mm] | W | 404.2 |
| | H | 330.0 |
| | D | 14.9 |
| Module Mass [g] | 1870 | |
| Operation Temperature Range [°C] | -20~70 | |
| Storage Temperature Range [°C] | -30~80 | |
| Surface Treatment | Anti-glare | |

Confidential